

PL LAMPS

FLEXCOLOR SWITCH BETWEEN CCTs

TYPE A + B / 2-PIN

						
LED-7313-G4	LED-7311-G4	LED-7314-G4	LED-7312-G4	LED-7322-G4	LED-7310-G4	LED-7316-G2
						
G23 3.5W REPLACES UP TO 9W	G23-2 7W REPLACES UP TO 26W	GX23 5.5W REPLACES UP TO 13W	GX23-2 7W REPLACES UP TO 26W	G24d 7W REPLACES UP TO 26W	G24d 9W REPLACES UP TO 26W	G24d 9W REPLACES UP TO 32W

TYPE A + B / 4-PIN

			
LED-7318-G2	LED-7328-G2	LED-7320-G4	LED-7324-G4
			
G24q/GX24q			
9W REPLACES UP TO 32W	16W REPLACES UP TO 42W	10W REPLACES UP TO 42W	9W REPLACES UP TO 42W

TYPE B / 4-PIN

				
LED-7340/43/44/45-G3	7340	43	44	45
				
2G11				
17W (7340) REPLACES UP TO 40W	16W (7343) REPLACES UP TO 36W	10W (7344) REPLACES UP TO 24W	8.5W (7345) REPLACES UP TO 18W	

RECOMMENDED MOUNTING ORIENTATION ↗ BASE UP ↘ BASE DOWN ↔ HORIZONTAL

PART #	REPLACES UP TO	WATTAGE	LUMENS	CCT	BASE	MOUNTING	DIMENSIONS
--------	----------------	---------	--------	-----	------	----------	------------

PL | UNIVERSAL | TYPE A+B | 2-PIN

LED-7310-FC-G4	26W / 2-PIN CFL	9W	1104-1243	FLEXCOLOR 2700K/3000K/3500K/4000K	G24d*		6.9" x 1.4"
LED-7311-FC1-G4		7W	900-950	FLEXCOLOR 3000K/3500K/4000K	G23-2		5.5" x 1.4"
LED-7312-FC1-G4					GX23-2		
LED-7313-FC-G4	9W / 2-PIN CFL	3.5W	389-428	FLEXCOLOR 2700K/3000K/3500K/4000K	G23		5.3" x 1.3"
LED-7314-FC-G4	13W / 2-PIN CFL	5.5W	628-696		GX23		7.0" x 1.4"
LED-7316-FC-G2	32W / 2-PIN CFL	9W	1050-1100	FLEXCOLOR 2700K/3000K/3500K/4000K/5000K	G24d*		6.8" x 2.4"
LED-7322-FC1-G4	26W / 2-PIN CFL	7W	900-950	FLEXCOLOR 3000K/3500K/4000K	G24d*		5.5" x 1.4"

PL | UNIVERSAL | TYPE A+B | 4-PIN

LED-7318-FC-G2	32W / 4-PIN CFL	9W	1050-1100	FLEXCOLOR 2700K/3000K/3500K/4000K/5000K	G24q GX24q**		6.8" x 2.4"
LED-7320-FC1-G4	42W / 4-PIN CFL	10W	1350-1460	FLEXCOLOR 3000K/3500K/4000K			6.6" x 1.4"
LED-7320-FC2-G4			1320-1460	FLEXCOLOR 2700K/4000K/5000K			
LED-7324-FC1-G4	42W / 4-PIN CFL	9W	1270-1360	FLEXCOLOR 3000K/3500K/4000K			5.7" x 1.3"
LED-7324-FC2-G4			1230-1360	FLEXCOLOR 2700K/4000K/5000K			
LED-7328-FC-G2	42W / 4-PIN CFL	16W	1750-1850	FLEXCOLOR 2700K/3000K/3500K/4000K/5000K			6.8" x 2.4"

PLL | BALLAST BYPASS | TYPE B

LED-7340-FC-G3	40W / 4-PIN CFL	17W	2024-2228	FLEXCOLOR 3000K/3500K 4000K/5000K/6500K	2G11		22" x 1.7"
LED-7343-FC-G3	36W / 4-PIN CFL	16W	1900-2000				16" x 1.7"
LED-7344-FC-G3	24W / 4-PIN CFL	10W	1180-1250				12" x 1.7"
LED-7345-FC-G3	18W / 4-PIN CFL	8.5W	930-980				8.5" x 1.7"

 OPEN FIXTURE ONLY  ENCLOSED FIXTURE RATED (MAY ALSO BE USED IN OPEN FIXTURE)

RECOMMENDED MOUNTING ORIENTATION  BASE UP  BASE DOWN  HORIZONTAL

* COMPATIBLE WITH BASE G24d-1, G24d-2 AND G24d-3

** COMPATIBLE WITH BASE G24q-1, G24q-2, G24q-3, GX24q-2, GX24q-3 AND GX24q-4

