

---

**RENEWABLES**

---

by **Light Efficient Design**

  
**Light Efficient Design**





CHOOSE FROM 6 MODELS – HID EQUIVALENCE UP TO 400W...

100% POWERED BY THE SUN – NO TRENCHING OR WIRING...



RP-SAL-8/30W





SCAN FOR POLE OFFERINGS + ACCESSORIES



SL-SAL-60L



OFF-GRID AREA LIGHTS

PART #	COMPARES TO	WATTAGE	LUMENS	CCT	EPA	DIMENSIONS	LISTINGS
RP-SAL-8W-50K-SF-GY-G2	70W HID	8W	1600	5000K	1.82	20.0" x 12.0" x 3.0"	<div>CE</div> <div></div> <div> 8801</div>
RP-SAL-8W-50K-SF-DB-G2							
RP-SAL-30W-50K-SF-GY-G2	250W HID	30W	6000	5000K	4.79	36.0" x 16.8" x 3.8"	
RP-SAL-30W-50K-SF-DB-G2							
● RP-SAL-8W-AMB-SF-GY-G2	70W HID	8W	284	580nm AMBER	1.82	20.0" x 12.0" x 3.0"	
● RP-SAL-8W-AMB-SF-DB-G2							
● RP-SAL-30W-AMB-SF-GY-G2	250W HID	30W	806		4.79	36.0" x 16.8" x 3.8"	
● RP-SAL-8W-AMB-SF-DB-G2							

OPERATING MODES |  TIMER |  MOTION SENSING

 TURTLE FRIENDLY ● GRAY ● DARK BRONZE  FOR LISTING STATUS GO TO LED-LLC.COM

OFF-GRID AREA LIGHTS

PART #	COMPARES TO	WATTAGE	LUMENS	CCT	EPA	DIMENSIONS	LISTINGS
 SL-SAL-60L-FC-T3-BK-G3	250W HID	30W	6000	FLEXCOLOR 3000K/4000K/5000K	4.5	36.0" X 26.0" X 32.0"	coming soon
 SL-SAL-OG-50W-50K-SF-BK-G2*	400W HID	50W	9800	5000K	6.1	11.2" x 7.0" x 16.3" (FIXTURE) 31.8" x 31.5" (SOLAR PANEL)	<div>CE</div> <div>FC</div>

OPERATING MODES |  TIMER |  MOTION SENSING

5  
YEAR  
WARRANTY

 CERTIFIED BATTERY	 BATTERY CHARGING TIME RP-SAL	 SL-SAL	 BATTERY CHARGING TEMP RP-SAL	 SL-SAL	 BATTERY LIFE	 REPLACEABLE BATTERY	 -4°F TO 122°F RP-SAL	 -40°F TO 140°F SL-SAL	 MOTION SENSING	 100,000hrs RATED LIFE
--	--	---	--	---	---	--	--	---	---	---

 EXCLUSIVE LONG-LASTING BATTERY  FOR LISTING STATUS GO TO LED-LLC.COM \* WHILE SUPPLIES LAST.





# INTELLIGENT MODULAR AREA LIGHT



PROFESSIONAL-GRADE, CONFIGURABLE, SOLAR- POWERED LIGHTING SYSTEM...





... ACCESS SOLERA  
CONNECT VIA THE WEB  
OR MOBILE APP

... MONITOR LIGHT LEVELS  
THROUGHOUT THE DAY

... MAP YOUR PROJECTS



EXAMPLE OF CUSTOMER DASHBOARD

INTELLIGENT MODULAR AREA LIGHT				
PART #	LUMENS	CCT	EPA	DIMENSIONS
SL-MA1-OG-1000634B1	ADJUSTABLE UP TO 10,000	FLEXCOLOR 3000K/4000K/5000K	8.0	SOLAR PANEL 27.1" x 19.2" x 2.2"
SL-MA1-HYB-1000634B1				
OPERATING MODES    CONSTANT BRIGHTNESS  MOTION SENSING				
<div><div> HYBRID   POWERED BY THE SUN &amp; BACKED UP BY LINE-VOLTAGE</div><div> OFF-GRID   100% POWERED BY THE SUN</div></div>				

STANDARD

OPTIONAL\*

CERTIFIED BATTERY

BATTERY CHARGE TIME

FULL POWER ALL NIGHT\*\*

BATTERY CHARGE TEMP

BATTERY LIFE\*\*

REPLACEABLE BATTERY

-40°F TO 140°F  
FIXTURE OPERATING TEMP

OPTIONAL MOTION SENSING

100,000hrs  
RATED LIFE

\* 10 YEAR WARRANTY AVAILABLE AT AN ADDITIONAL COST. \*\*BATTERY LIFE DEPENDS ON ENVIRONMENT AND POWER SETTINGS

**BUILD AND REMOTELY PROGRAM, CONTROL AND MONITOR AN INTELLIGENT SOLAR LIGHTING NETWORK. GRAPHICALLY SHOW USAGE AND DEMAND. TRACK SOLAR ENERGY GENERATION FOR SUSTAINABILITY REPORTING AND POSSIBLE TAX CREDITS.**

**CONFIGURE THE INTELLIGENT MODULAR AREA LIGHT TO FIT YOUR APPLICATION** Area lighting, pedestrian lighting, billboard lighting and more. Available as a retrofit kit for sites with existing poles or purchase with pole kit, if needed.

**REMOTELY SET UP YOUR NETWORK W/ SOLERA CONNECT** Create one or more projects. Preset programming modes make programming lights and sensor settings quick and easy. Site grouping and custom control setup.

**BI-DIRECTIONAL COMMUNICATION OVER A CELLULAR NETWORK** Allows for remote monitoring and control of the solar collection, battery state, and lighting parameters. Each light included in a project is individually accessible. Get status updates to be alerted to unexpected conditions.






IMPROVE PEDESTRIAN SAFETY...



SL-SBL-2W

OFF-GRID BOLLARD LIGHT					
PART #	COMPARES TO	LUMENS	CCT	DIMENSIONS	LISTINGS
SL-SBL-2W-27K-BK-G1	30W HALOGEN	266	2700K	8.0" x 30.0"	CE FCC
SL-SBL-2W-40K-BK-G1			4000K		
OPERATING MODE					
		 DUSK TO DAWN			



3  
YEAR  
WARRANTY



8-9  
HRS  
BATTERY  
CHARGE TIME



32°F  
TO  
149°F  
BATTERY  
CHARGING TEMP



UP TO  
18  
HRS  
BATTERY LIFE



120°  
BEAM ANGLE



-13°F TO 140°F  
OPERATING TEMP




100,000hrs  
RATED LIFE

THREE UNIQUE MODELS, PERFECT FOR PATHWAYS, PIERS AND MORE...



SL-SPT-20W

OFF-GRID POST TOP LIGHT						
PART #	COMPARES TO	LUMENS	CCT	DIMENSIONS	EPA	LISTINGS
SL-SPT-20W-30K-SF-G2	150W HID	2000	3000K	16.0" x 32.0"	2.2	CE FCC
SL-SPT-20W-40K-SF-G2			4000K			
OPERATING MODES						
☀️ DUSK TO DAWN   ⌚ TIMER   🚶 MOTION SENSING				SCAN FOR POLE OFFERINGS + ACCESSORIES		
						



3  
YEAR  
WARRANTY



7-8  
HRS  
BATTERY  
CHARGE TIME



32°F  
TO  
149°F  
BATTERY  
CHARGING TEMP



UP TO  
30  
HRS  
BATTERY LIFE



360°  
BEAM ANGLE




-4°F TO 149°F  
OPERATING TEMP



100,000hrs  
RATED LIFE



SL-CPT

OFF-GRID PATHWAY LIGHT						
PART #	COMPARES TO	LUMENS	CCT	DIMENSIONS	EPA	LISTINGS
SL-CPT-25L-30K-BK-G1	150W	2500	3000K	21.3" x 13.4"	1.0 SF	CE FCC
SL-CPT-25L-40K-BK-G1			4000K			
OPERATING MODES			SCAN FOR POLE OFFERINGS + ACCESSORIES			
☀️ CONSTANT BRIGHTNESS   ⌚ TIMER   🚶 MOTION SENSING						
						



3  
YEAR  
WARRANTY



7-8  
HRS  
BATTERY  
CHARGE TIME



32°F  
TO  
122°F  
BATTERY  
CHARGING TEMP



UP TO  
30  
HRS  
BATTERY LIFE\*



160°  
BEAM ANGLE



-4°F TO 122°F  
OPERATING TEMP



50,000hrs  
RATED LIFE

\* ON 2HR + SENSOR MODE.



...ADJUSTABLE – LIGHT EXACTLY WHERE YOU NEED IT



SL-SFL-20W

OFF-GRID FLOOD LIGHT

PART #	COMPARES TO	LUMENS	CCT	DIMENSIONS	ADJ HEIGHT	LISTINGS
SL-SFL-20W-40K-BK-G2	150W HID	2000	4000K	26.0" x 11.0" (PANEL w/ LIGHT)	16" TO 21"	CE FC

OPERATING MODE

 CONSTANT BRIGHTNESS |  TIMER



SL-SDL-20W

OFF-GRID DISPLAY LIGHT

PART #	COMPARES TO	LUMENS	CCT	DIMENSIONS	LISTINGS
SL-SDL-2FT-40K-BK-G2	70W HID	750	4000K	23.6" x 4.3" x 4.3"	CE FC
SL-SDL-4FT-40K-BK-G2	150W HID	2000	4000K	47.2" x 4.3" x 4.3"	

ACCESSORIES

RP-SDL-BK-LB | 7" CLAMP MOUNT BRKT (2 PK)

OPERATING MODES

 CONSTANT BRIGHTNESS |  TIMER

SURFACE MOUNT BRACKET INCLUDED



3 YEAR WARRANTY



8-9 HRS BATTERY CHARGE TIME



32°F TO 115°F BATTERY CHARGING TEMP



UP TO 24 HRS BATTERY LIFE



120° BEAM ANGLE



-4°F TO 140°F OPERATING TEMP



50,000hrs RATED LIFE



3 YEAR WARRANTY



8-9 HRS BATTERY CHARGE TIME



32°F TO 113°F BATTERY CHARGING TEMP



UP TO 24 HRS BATTERY LIFE



120° BEAM ANGLE



-4°F TO 140°F OPERATING TEMP



50,000hrs RATED LIFE

USE LIGHT ENGINE AS A POWER BANK...



SL-SMFL-10W

OFF-GRID MULTIFUNCTIONAL FLOOD LIGHT

PART #	COMPARES TO	LUMENS	CCT	DIMENSIONS	LISTINGS
SL-SMFL-10W-40K-BK-G1	70W HID	1100	4000K	9.1" x 6.5" (LIGHT) 13.6" x 9.3" (PANEL)	CE FC

OPERATING MODES

 CONSTANT BRIGHTNESS |  TIMER |  MOTION SENSING



3 YEAR WARRANTY



8-9 HRS BATTERY CHARGE TIME



32°F TO 140°F BATTERY CHARGING TEMP



UP TO 24 HRS BATTERY LIFE



90° BEAM ANGLE



-4°F TO 140°F OPERATING TEMP



50,000hrs RATED LIFE





...ALL-IN-ONE DESIGN



MAKE IT MAGNETIC ↓

DETACHABLE SOLAR PANEL...

BUILT TO WITHSTAND  
EXTREME CLIMATES



SL-SWL-15W ↑



SL-SWL-16L ↑

OFF-GRID WALL PACK

PART #	COMPARES TO	LUMENS	CCT	DIMENSIONS	LISTINGS
SL-SWL-15W-40K-BK-G2	100W HID	1500	4000K	10.0" x 12.0"x 5.0"	CE FCC
SL-SWL-15W-40K-BK-G2-M					

OPERATING MODES

☀️ DUSK TO DAWN | ⌚ TIMER | 🚶 MOTION SENSING

OFF-GRID FLEXCOLOR WALL PACK

PART #	COMPARES TO	LUMENS	CCT	DIMENSIONS	LISTINGS
SL-SWL-16L-FC-BK-G3	100W HID	1600	FLEXCOLOR 3000K/4000K/5000K	13.0" X 12.0" X 5.0"	CE FCC
SL-SWL-16L-FC-BK-G3-M					

OPERATING MODES

☀️ CONSTANT BRIGHTNESS | 🚶 MOTION SENSING

3 YEAR WARRANTY

7 HRS BATTERY CHARGE TIME

32°F TO 149°F BATTERY CHARGING TEMP

UP TO 50 HRS BATTERY LIFE

100° BEAM ANGLE

5°F TO 113°F OPERATING TEMP

35,000hrs RATED LIFE



U EACH MAGNET HOLDS UP TO 35 LBS. FOR A TOTAL PULL STRENGTH OF 140 LBS.

U MAGNETIC MOUNTING



--- DETACHABLE SOLAR PANEL

U MAGNETIC MOUNTING

3 YEAR WARRANTY

7 HRS BATTERY CHARGE TIME

4°F TO 140°F BATTERY CHARGING TEMP

UP TO 25 HRS BATTERY LIFE

120° BEAM ANGLE

-40°F TO 140°F OPERATING TEMP

50,000hrs RATED LIFE



**R40 / R48**  
NON-NETWORKED  
RFID CHARGING\*  
UP TO 48A  
CHARGING POWER

**S48**  
NON-NETWORKED  
PLUG + CHARGE  
UP TO 48A CHARGING POWER



**P48 / P80**  
NETWORKED  
SMART CHARGING  
UP TO 48A  
CHARGING POWER

**ampUp**  
PRO INCLUDED  
W/ P48 + P80  
(SEE PAGE 10)



**P80d**  
DUAL PORT SMART  
CHARGING  
UP TO 80A  
CHARGING POWER

POWERED BY  
**AUTEL**

**D-SERIES**  
DC COMPACT  
CHARGER / 40kW  
PROVIDES UP TO  
80 MILES OF RANGE IN  
30 MINUTES



**F-SERIES**  
DC HiPOWER CHARGER  
480KW-640kW  
PROVIDES UP TO 250 MILES  
OF RANGE IN 10 MINUTES

**C-SERIES**  
DC FAST CHARGER  
60kW-240kW  
PROVIDES UP TO  
125 MILES OF RANGE IN  
10 MINUTES



POWERED BY **AUTEL**

\* 5 RFID CARDS INCLUDED.



LEVEL 2, NON-NETWORKED CHARGING





INSTALL ON A PEDESTAL  
OR WALL MOUNT...



3  
YEAR  
WARRANTY



200-  
240V AC



11.5  
kW  
S48  
MAX OUTPUT



9.6  
kW  
R40  
MAX OUTPUT









11.5  
kW  
R48  
MAX OUTPUT








SCAN FOR MORE  
INFO ON PEDESTALS +  
MOUNTING OPTIONS

NO NETWORK NEEDED – SIMPLY PLUG + CHARGE



PART #	CHRG AMPS	CONNECTOR	NETWORK	USER INTERFACE	OCPP SOFTWARE	UNIT DIMENSIONS	LISTINGS
R40   ALL-IN-ONE KIT (INCLUDES CHARGER W/ 18 FT OR 25 FT, 10AWG, 40A CABLE)							
EVC-L2-R40-18	UP TO 40A	SAE J1772	RFID	N/A	N/A	9.8" x 14.2" x 3.9"	 
EVC-L2-R40-25							
R48   ALL-IN-ONE KIT (INCLUDES CHARGER W/ 18 FT OR 25 FT, 8AWG, 48A CABLE)							
EVC-L2-R48-18	UP TO 48A	SAE J1772	RFID	N/A	N/A	9.8" x 14.2" x 3.9"	 
EVC-L2-R48-25							
R40 / R48   IN THE BOX							
	18 FT (R40-18/R48-18) OR 25 FT (R40-25/R48-25) OUTPUT CORD W/ SAE J1772 CONNECTOR			5 RFID CARDS		MOUNTING HARDWARE + INSTRUCTIONS	

\* 5 YEAR EXTENDED WARRANTY AVAILABLE. CONTACT SALES REPRESENTATIVE

PART #	CHRG AMPS	CONNECTOR	NETWORK	USER INTERFACE	OCPP SOFTWARE	UNIT DIMENSIONS	LISTINGS
S48   ALL-IN-ONE KIT (INCLUDES CHARGER W/ 18 FT OR 25 FT, 8AWG, 48A CABLE)							
EVC-L2-S48-18	UP TO 48A	SAE J1772	N/A	N/A	N/A	8" x 9.2" x 4"	 
EVC-L2-S48-25							
S48   IN THE BOX							
	1 FT INPUT CORD W/ NEMA 14-50 PLUG (ATTACHED TO UNIT)					CABLE HOOK W/ HOLSTER + BACKPLATE	MOUNTING HARDWARE + INSTRUCTIONS
LEVEL 2 EV CHARGER TESTER							
PART #	DESCRIPTION						
EVC-L2-ACC-TESTER-J1772	VERIFY THE CORRECT OPERATION AND SETTING OF AN EV CHARGER AFTER INSTALLATION, W/O AN ELECTRIC VEHICLE PRESENT						





LEVEL 2, NETWORKED SMART CHARGING

PERFECT FOR  
MULTI-UNIT HOUSING,  
OR RETAIL PROPERTIES...



200-240V AC



NETWORK  
CONNECTIVITY



11.2  
kW  
P48  
MAX OUTPUT



19.2  
kW  
P80  
MAX OUTPUT










EQUIPPED W/ LCD SCREEN, RFID, OCPP NETWORK

INSTALL ON A  
PEDESTAL OR  
WALL MOUNT...



SCAN FOR MORE  
INFO ON PEDESTALS +  
MOUNTING OPTIONS



PART #	CHRG AMPS	CONNECTOR	CABLE LENGTH	NETWORK	USER INTERFACE	OCPP SOFTWARE	UNIT DIMENSIONS	LISTINGS
P48   ALL-IN-ONE KITS (INCLUDES CHARGER W/ 48A CABLE SET)								
 EVC-L2-48A-L1-1-4G-D	UP TO 48A	SAE J1772	18FT	ETHERNET/RFID/4G	LCD DISPLAY	1YR AMPUP PRO	9.8" x 13.8" x 5.1"	 
 EVC-L2-48A-L1-1-4G-D-25			25FT					
P80   ALL-IN-ONE KIT (INCLUDES CHARGER W/ 80A CABLE SET)								
 EVC-L2-P80-18-AP1	UP TO 80A	SAE J1772	18FT	ETHERNET/RFID/4G	LCD DISPLAY	1YR AMPUP PRO	9.8" x 13.8" x 5.1"	 

PART #	DESCRIPTION	PART #	DESCRIPTION
PEDESTALS / ACCESSORIES			
EVC-L2-ACC-LPK2	LOWER PEDESTAL KIT FOR L2 CHARGER	EVC-L2-ACC-CM	CABLE MGMT FOR PEDESTAL W/ 2 RETRACTORS
EVC-L2-ACC-SSB	BRACKET FOR SIDE-BY-SIDE CHARGERS	EVC-L2-ACC-CM1	CABLE MGMT FOR PEDESTAL W/ 1 RETRACTOR
EVC-L2-ACC-ANCHOR KIT WET	WET CONCRETE ANCHOR KIT	EVC-L2-ACC-CMR	CABLE RETRACTOR W/ SPRING LOADED TETHER
EVC-L2-ACC-MAKE READY BASE	CHARGING STATION FOUNDATION	EVC-L2-ACC-HAD	HOOK/HOLSTER FOR WALL MOUNTING

LEVEL 2 EV CHARGER TESTER	
PART #	DESCRIPTION
EVC-L2-ACC-TESTER-J1772	VERIFY THE CORRECT OPERATION AND SETTING OF AN EV CHARGER AFTER INSTALLATION, W/O AN ELECTRIC VEHICLE PRESENT





LEVEL 2, NETWORKED SMART CHARGING



8-INCH HD  
ADVERTISING  
SCREEN...

UNIT W/ PEDESTAL  
MOUNT SHOWN...

EQUIPPED W/ LCD SCREEN, RFID, OCPP NETWORK



PART #	MODEL #	DESCRIPTION
P80D		
BEV-L2-P80D-18-CM-P	MU38FP5C	DUAL 80A CHARGER, 18 FT 80A CABLE SET, 4G CELLULAR, POS, PEDESTAL MOUNT, CABLE MANAGMENT
BEV-L2-P80D-18	UF38C001	DUAL 80A CHARGER, 18 FT 80A CABLE SET, 4G CELLULAR, WALL-MOUNT
BEV-L2-P80D-25-CM-P	MU38FP7C	DUAL 80A CHARGER, 25 FT 80A CABLE SET, 4G CELLULAR, POS, PEDESTAL MOUNT, CABLE MANAGMENT
BEV-L2-P80D-25	UF38L001	DUAL 80A CHARGER, 25 FT 80A CABLE SET, 4G CELLULAR, WALL-MOUNT

PART #	MODEL #	DESCRIPTION
ACCESSORIES		
BEV-L2-P80D-PP	FPP	P80 PEDESTAL POST
BEV-L2-P80D-CM6	CMSB2	D80P-18 6 FT CABLE MANAGEMENT SYSTEM
BEV-L2-P80D-CM9	CMSA2	D80P-25 9 FT CABLE MANAGEMENT SYSTEM
BEV-L2-P80D-POS	POSA	D80P POS TERMINAL



LEVEL 3, NETWORKED SMART CHARGING



...INSTALL ON A PEDESTAL  
OR MOVABLE TROLLEY

...FOR PEOPLE & BUSINESSES WHERE  
TIME IS THE MOST VALUED ASSET

PART #	MODEL #	DESCRIPTION
C-SERIES DC COMPACT CHARGER		
BEV-L3-C40-25-PM	DC40APN25	DUAL 40KW COMPACT DCFC 25 FT PEDESTAL MOUNT CABLE/CCS1
BEV-L3-C40-25-PPM	DC40APC25	DUAL 40KW COMPACT DCFC 25 FT PEDESTAL MOUNT CABLE/CCS1 W/ POS
BEV-L3-C40-25-T	DC40ATN25	DUAL 40KW COMPACT DCFC 25 FT TROLLEY CABLE/CCS1

PART #	MODEL #	DESCRIPTION
D-SERIES DC FAST CHARGER		
BEV-L3-D60	UF060A3001	60KW UL DUAL PORT DCFC
BEV-L3-D120	UF120A3001	120KW UL DUAL PORT DCFC
BEV-L3-D180L	UF180A4001	180KW UL DUAL PORT DCFC
BEV-L3-D240L	UF240A4001	240KW UL DUAL PORT DCFC



...PERFECT FOR HIGHWAY REST-STOP,  
GAS STATIONS AND FLEET MANAGEMENT

PART #	MODEL #	DESCRIPTION
F-SERIES DC HI-POWER CHARGER		
BEV-L3-F480-2B	US480A2L0	480KW DCFC, 2 DISPENSERS 4 PORTS: BOOST 16 FT CABLE/CCS1 CABLE MANAGEMENT
BEV-L3-F480-2LC	US480A0L2	480KW DCFC, 2 DISPENSERS 4 PORTS: LIQUID COOLED 16 FT CABLE/CCS1 CABLE MANAGEMENT
BEV-L3-F640-2B	US640A2L0	640KW DCFC, 2 DISPENSERS 4 PORTS: BOOST 16 FT CABLE/CCS1 CABLE MANAGEMENT
BEV-L3-F640-2LC	US640A0LC2	640KW DCFC, 2 DISPENSERS 4 PORTS: LIQUID COOLED 16 FT CABLE/CCS1 CABLE MANAGEMENT

INCLUDES...  
2 POWER DISPENSERS  
AND A NONDESCRIPT  
POWER CABINET.





CORPORATE HQ & TRAINING CENTER • CARY, IL | INNOVATION & MANUFACTURING CENTER • Middleton, MA  
847.380.3540 • [led-llc.com](http://led-llc.com) • [sales@led-llc.com](mailto:sales@led-llc.com)



[solera-solar.com](http://solera-solar.com)



[breez-EV.com](http://breez-EV.com)