



SERIES	CONTROL IMAGE	ADDER OR LED PN	DESCRIPTION	REMOTE	ICON
TTV/TF		-OCC	Passive infrared and daylight harvesting occupancy sensor	IR12	
		-BT	Silvair-ready Bluetooth control node	NA	
		-OCCBT	Silvair-ready passive infrared and daylight harvesting occupancy sensor	NA	
TV/TF		-OCC	Passive infrared and daylight harvesting occupancy sensor	IR12	
		-OCCBT	Silvair-ready passive infrared and daylight harvesting occupancy sensor	IR12	
TRV/TRF		-OCC	Passive infrared and daylight harvesting occupancy sensor	IR12	
		-OCCBT	Silvair-ready passive infrared and daylight harvesting occupancy sensor	IR12	
LBI		RP-LBI-OC2-A	In-line microwave and daylight harvesting occupancy sensor	IR11	
		RP-LBI-PIR-A	In-line passive infrared occupancy sensor	IR11	
		RP-LBI-BLE-OC	In-line Silvair-ready Bluetooth microwave occupancy sensor	NA	
		RP-LBI-BLE-A	In-line Silvair-ready Bluetooth control node	NA	
		RP-LBI-BLE-PIR-A	In-line Silvair-ready Bluetooth control node w/ passive infrared occupancy sensor	NA	
LBI65		RP-LBI65-PIR-A	IP65 In-line passive infrared occupancy sensor	IR11	
		RP-LBI65-BLE-A	IP65 In-line Silvair-ready Bluetooth control node	NA	
		RP-LBI65-BLE-PIR-A	IP65 In-line Silvair-ready Bluetooth control node w/ passive infrared occupancy sensor	NA	
LBIMAX		-OCC	Microwave and daylight harvesting occupancy sensor	IR12	
		-OCBT	Silvair-ready Bluetooth microwave occupancy sensor	IR12	
		-BT	Silvair-ready Bluetooth node w/ external antenna	NA	
LS STRIP		-OCC	Microwave and daylight harvesting occupancy sensor	IR12	
		-OCBT	Silvair-ready Bluetooth microwave occupancy sensor	IR12	
		-BT	Silvair-ready Bluetooth node w/ external antenna	NA	
LIVC		-OCC	Microwave and daylight harvesting occupancy sensor	IR12	
		-OCBT	Silvair-ready Bluetooth microwave occupancy sensor	IR12	
		-BT	Silvair-ready Bluetooth node w/ external antenna	NA	
LBE		RC-OCC-HNS111-A	Microwave and daylight harvesting occupancy sensor	IR12	
		RC-OCLR-HNS111LR-A	Limited-range microwave and daylight harvesting occupancy sensor (no mounting feet)	NA	
		RC-OMWBT-MW-7-BLE-SR	Silvair-ready Bluetooth microwave and daylight harvesting occupancy sensor	IR12	
	COMING SOON	RC-OCBT-HNB115MW	Silvair-ready Bluetooth microwave and daylight harvesting occupancy sensor	NA	
		RC-OCCBT-HNB131PIR	Silvair-ready Bluetooth passive infrared and daylight harvesting occupancy sensor (external fixture mount only)	NA	
		RC-BT-HNB131CTL	Silvair-ready Bluetooth control node	NA	
		RC-OCCBT-ARM-HNB178-PIR-BLE	Silvair-ready Bluetooth passive infrared external arm sensor	NA	
	RC-BTX-HNB136	Silvair-ready Bluetooth node w/ external antenna	NA		



SIMPLE OCC SENSOR



NLC OCCUPANCY SENSOR



NLC NODE



SERIES	CONTROL IMAGE	ADDER OR LED PN	DESCRIPTION	REMOTE	ICON
		-OCC	Microwave and daylight harvesting occupancy sensor	IR12	
		-OCLR	Limited-range microwave and daylight harvesting occupancy sensor (no mounting feet)	IR12	
		-OCBT	Silvair Ready Bluetooth microwave and daylight harvesting occupancy sensor	IR12	
		-BT	Silvair-ready Bluetooth control node	NA	
		-BTX	Silvair-ready Bluetooth control node with external antenna	NA	
		-OC1	Microwave and daylight harvesting occupancy sensor	IR12	
		-OCLR	Limited-range microwave and daylight harvesting occupancy sensor (no mounting feet)	IR12	
		-OCBT	Silvair-ready Bluetooth microwave and daylight harvesting occupancy sensor	IR12	
		-BT	Silvair-ready Bluetooth control node	NA	
		-BTX	Silvair-ready Bluetooth control node with external antenna	NA	

SIMPLE OCC SENSOR
 NLC OCCUPANCY SENSOR
 NLC NODE

SERIES	LED PN	COMPATIBILITY
	RC-REMOTE-IR11	LBI-OC2, LBI65 PIR Remote
	RC-REMOTE-IR12	HNS111- LS, LBIMAX, LIVC, CR/SR

EXTERNAL LOAD CONTROLS, SWITCHES, AND SENSORS

PICTURE	LED PN	DESCRIPTION
FIXTURE MOUNTED CONTROLS		
	RP-BRI819P-B-D-BLE	Silvair ready Bluetooth PIR dimming occupancy sensor, BRI819P-B-D-BLE standard, 120-277VAC
	RP-BRI819P-B-D-P-BLE	Silvair ready IP65 Bluetooth PIR dimming occupancy sensor, BRI819P-B-D-BLE standard, 120-277VAC
	RP-PSC-BL-I-FM-110-BLE-SR	Passive infrared bi-level dimming occupancy sensor, line voltage, TruBlu™
	RP-PSC-WCM-450-BLE-SR	TruBlu SIG mesh room controller, 120-277 Volt with dimming, 12 Volt aux, sensor input, 20A relay
DIMMERS AND WALL SENSORS		
	RP-PSC-DM-WS-100-BLE-SR	TruBlu SIG mesh dimming wall switch, 120-277V
	RP-PSC-DM-I-WS-100-BLE-SR	TruBlu SIG mesh dimming wall sensor switch, 120-277V
	RP-PSC-EO-WS-100-BLE	Batteryless EnOcean switch, single rocker
	RP-PSC-EO-WS-400-BLE	Batteryless EnOcean switch, double rockers
	RP-ENOCEAN-ESRPB-W-EO	Easyfit single rocker pad for EnOcean radio
	RP-EDRPB-W-EO	Easyfit double rocker pad for EnOcean radio