





FLEXCOLOR A21/23 HIGH OUTPUT





<- safe for use in enclosed fixtures</p>

- -> Frosted design to reduce glare.
- -> 360° light output for optimal performance.
- -> Switch between 3000K, 4000K, & 5000K right on the unit.
- Pretested & potted drivers are burnt in 3x prior to shipping and protected against vibration & moisture.
- -> Engineered to work efficiently in enclosed fixtures & damp environments.
- -> Protected against insects & dust.
- -> Lamps are Shatter-Resistant made from polycarbonate plastic which is a highly shatter resistant material.
- Models 35W and above dim to 50% by the switch located on the side of the lamp only (stepped dimmable by other wired communication protocol)





flexcolor ->

switch between

color

temps





INSTALL



MEDIUM +



VERTICAL MOUNTING



CRI



OPERATING



ENCLOSED



50,000hrs



INGRESS PROTECTION

PART #	UPC	REPLACES	WATTAGE	LUMENS	COLOR (K)	BASE
LED-8017E345-G3	844006080143	150W INC	20W	2400/2700/2600	3000K/4000K/5000K	E26
LED-8018E345-G3	844006080181	200W INC	25W	3000/3375/3250	3000K/4000K/5000K	E26
LED-8019E345-G3	844006080198	300W INC	35W	4200/4725/4550	3000K/4000K/5000K	E26
LED-8019M345-G3	844006080204	175W HID	35W	4200/4725/4550	3000K/4000K/5000K	EX39
LED-8020M345-G3	844006080211	250W HID	45W	5400/6075/5850	3000K/4000K/5000K	EX39
LED-8021M345-G3	844006080228	320W HID	65W	7800/8775/8450	3000K/4000K/5000K	EX39

* dimensions on page 2















A21/23 HIGH OUTPUT



