



SPEC SHEET

LINKABLE BAR / INTERNAL DRIVER IP65 (LBI 65)

IP65
RATED

NSF

IK08
RATED

WATERPROOF LINKING — CONNECT UP TO 40 BARS*

PERFECT FOR OUTDOOR CANOPIES AND MORE!

LIQUID-TIGHT END CAPS / WET-LISTED BARS + SENSORS / VAPOR-TIGHT / POLYCARBONATE LENS

SUPERFLEX SWITCH BETWEEN 4 WATTAGES & 6 CCTS
2700K / 3000K / 3500K / 4000K / 5000K / 5700K



12V AUX OUTPUT



EFFICACY
(LIGHT ENGINE)



CRI



BEAM ANGLE



OPERATING TEMP
-22°F TO 122°F



>42,000hrs
RATED LIFE

RemPhos
by Light Efficient Design

LIGHT EFFICIENT DESIGN • sales@led-llc.com • led-llc.com

* CONNECT UP TO 33 4FT UNITS TOGETHER @ 120VAC OR 40 4FT UNITS @ 277VAC.

LINKABLE BAR / INTERNAL DRIVER IP65 (LBI 65)

UNLIMITED APPLICATIONS...

COOLERS



- SHATTERPROOF CONSTRUCTION
- CONTAMINATE-RESISTANT
- LIQUID-TIGHT END CAPS

FOOD PROCESSING FACILITIES



- CONNECT UP TO 40*
- POLYCARBONATE LENS
- VAPOR-TIGHT

PARKING GARAGES



- TAMPER-RESISTANT
- LIQUID-TIGHT END CAPS
- WET-LISTED SENSORS

ACCESSORIES (SEE SPEC SHEET FOR FULL LINE OF ACCESSORIES)

AIRCRAFT SUSPENSION CABLE



10 FT STAINLESS STEEL + WATERPROOF

INCOMING POWER



3 FT CABLE WIRE WHIP



CONDUIT ADAPTER

UP TO 48 IN



LINKING CABLE

CONNECTORS



DIMMABLE W/CCT



NON-DIMMABLE

SEAMLESS CONNECTORS

REMOTE CONTROL



IRWC
(INCLUDED W/ EVERY BAR)

OPTIONAL REMOTE EMERGENCY BATTERY BACK UP**



RP-LBI-EMG2-8W-DIM
(8W / DIMMABLE)



RP-LBI-EMG2-25W-DIM
(25W / DIMMABLE)

SIMPLE LIGHTING CONTROL

RP-LBI65-PIR-A

IP65 IN-LINE PASSIVE
INFRARED OCCUPANCY SENSOR



NETWORK LIGHTING CONTROLS

RP-LBI65-BLE-PIR-A

IP65 IN-LINE SILVAIR-READY BLUETOOTH CONTROL NODE
W/ PASSIVE INFRARED OCCUPANCY SENSOR



RP-LBI65-BLE-A

IP65 IN-LINE SILVAIR-READY
BLUETOOTH CONTROL NODE



RemPhos
by Light Efficient Design

LIGHT EFFICIENT DESIGN • sales@led-llc.com • led-llc.com

* CONNECT UP TO 33 4FT UNITS TOGETHER @ 120VAC OR 40 4FT UNITS @ 277VAC. ** EMERGENCY BATTERY BACKUP IS FOR INDOOR USE ONLY.